

I/O Cards	Mic/Line Input Card CIML4	High-Performance Mic/Line Input Card CIML4-HP	Line Output Card COL4	DataPort Output Card CODP4
Description	Four channels of microphone/line-level analog audio input with 48V phantom power	Four channels of microphone/line-level analog audio input with 48V phantom power and high performance pre-amplifiers and A/D converters	Four channels of balanced, line-level analog output	Four audio output channels (2 DataPorts) for connection to DataPort equipped QSC amplifiers
Performance				
Dynamic Range Unweighted	> 105 dB	> 112 dB	> 112 dB	> 114 dB
Dynamic Range A-weighted	> 108 dB	> 115 dB	> 115 dB	> 117 dB
Distortion 20 Hz – 20 kHz +4 dBu (nominal input)	< 0.009% THD+N	< 0.004% THD+N	–	–
Distortion 20 Hz – 20 kHz 2 dB below clip (max)	< 0.08% THD+N	< 0.06% THD+N	< 0.004% THD+N	< 0.004% THD+N
Crosstalk 20 Hz – 20 kHz				
Inter-channel (max)	> 100 dB	> 110 dB	> 100 dB	> 95 dB
Inter-channel (typ)	> 110 dB	> 110 dB	> 110 dB	> 100 dB
Intra-channel (max)	> 100 dB	> 110 dB	> 100 dB	> 100 dB
Intra-channel (typ)	> 110 dB	> 110 dB	> 110 dB	> 110 dB
Frequency Response 20 Hz – 20 kHz (max)	± 0.5 dB	± 0.5 dB	± 0.5 dB	± 0.5 dB
Frequency Response 20 Hz – 20 kHz (typ)	± 0.2 dB	± 0.2 dB	± 0.2 dB	± 0.2 dB
Input Impedance				
Balanced (nominal)	10 k ohms	10 k ohms	–	–
Unbalanced (nominal)	10 k ohms	10 k ohms	–	–
Common Mode Rejection 20 Hz – 20 kHz (max)	> 45 dB	> 45 dB	–	–
Common Mode Rejection 20 Hz – 20 kHz (typ)	> 50 dB	> 50 dB	–	–
Max Input Level	0.123, 2.25, 8.70, 17.35 Vrms -16, 10, 21, 27 dBu -18.2, 7.04, 18.8, 24.78 dBv (4 selections)	1.23 to 17.35 Vrms -56 to 27 dBu -58.2 to 24.8 dBv (continuously variable)	–	–
Mute	Infinite attenuation (via digital mute)	Infinite attenuation (via digital mute)	Infinite attenuation (via electro-mechanical relays)	Infinite attenuation (via electro-mechanical relays)
Audio Converters				
Analog to Digital Conversion (ADCs)	24-bit delta-sigma at 48 or 96 kHz sample rate	24-bit delta-sigma at 48 or 96 kHz sample rate	–	–
Digital to Analog Conversion (DACs)	–	–	24-bit delta-sigma at 48 or 96 kHz sample rate	24-bit delta-sigma at 48 or 96 kHz sample rate
Group Delay	< 13 FS (≈ 271 μs) at 48 kHz	< 13 FS (≈ 271 μs) at 48 kHz	< 10 FS (≈ 196 μs) at 48 kHz	< 13 FS (≈ 271 μs) at 48 kHz
Connectors	Four 3-terminal Euro-style detachable terminal blocks	Four 3-terminal Euro-style detachable terminal blocks	Four 3-terminal Euro-style detachable terminal blocks	Two 15-pin HD15 connectors
User-configurable Options (software enabled)				
Phantom Power	+48 V phantom power (meets IEC 1938 [1996] spec)	+48 V phantom power (meets IEC 1938 [1996] spec)	–	–
Output Trim				
Vrms (max)	–	–	8.7 V	–
dBu (max)	–	–	21 dBu	–
dBv (max)	–	–	18.8 dBv	–
Amplifier Standby	–	–	–	Set or clear amplifier in standby mode
Mute	–	–	–	Set or clear individual channel mutes
Enable Meters	–	–	–	Enable data collection of meters for each channel
Audio Output Levels	–	–	–	Adjust individual audio channel levels
Amplifier Model Support	–	–	–	CX, PowerLight™ 3 Series, DCA, and legacy V1 models

I/O Cards	AES-3 Input/Output Card CAES4	CobraNet Bridge Card CCN32
Description	Four input and four output channels of AES-3 digital audio	Up to 32 input and 32 output channels of CobraNet digital audio
Frequency Response	± 0.2 dB	± 0.2 dB
Mute	Infinite attenuation (via digital mute)	Infinite attenuation (via digital mute)
Group Delay	37 Samples (0.760 ms actual) with Sample Rate Converter enabled	Selectable: 64 Samples (2.687 ms actual) 128 Samples (4.020 ms actual) 256 Samples (6.686 ms actual)
I/O Capacity	4x4	Selectable: 4x4 8x8 16x16 32x32 (in Core only)
Bundle Packing	–	0 to 8 channels
Network Transmitters	–	4
Network Receivers	–	4
Management	–	CobraNet management via SNMP
Connectors	Four 3-terminal Euro-style detachable terminal blocks	Dual RJ-45



Mic/Line Analog Input Card



High-Performance Mic/Line Analog Input Card



Analog Line Output Card



DataPort Output Card



AES-3 Digital Input/Output Card



CobraNet™ Digital Input/Output Card



1675 MacArthur Boulevard • Costa Mesa, CA 92626 • Ph: 800/854-4079 or 714/957-7100 • Fax: 714/754-6174

© 2012 QSC Audio Products, LLC. All rights reserved. QSC and the QSC logo are registered trademarks of QSC Audio Products, LLC in the U.S. Patent and Trademark office and other countries. Q-Sys is a trademark of QSC. Intel and the Intel logo are registered trademarks of the Intel corporation.

I/O Card Spec Sheet 12/21/12



please recycle