

— — — I M E — X

FX BatmooZ



Designed in
Germany



FEIMEX FX BatmooZ

The portable and battery-powered LED lamp is equipped with 4x 10W RGBW LEDs and provides with the lightweight design the ideal solution for an optimum illumination without cable.

FX BatmooZ



Portable, battery-powered LED lamp with IP65 motorized zoom

The FX BatmooZ is a portable, battery-powered LED-Light which can be applied without DMX- or Powercabling. So your location is in perfect light within a few seconds and valuable construction time can be saved.


With the motorized zoom and an angle between 8 ° and 40 ° several incredible effects and insersts can be made. This fact makes the FX BatmooZ unique.

A further highlight is the W-DMX-Receiver which makes it possible to use and control the FX BatmooZ without any cables. It is also possible to create your own personal scenes or use a lot of colours stored in the internal library. These functions are making the battery-powered LED lamp the most flexible device on the market.

The FX BatmooZ can be customized in any surrounding. The standard-colour of the product is black but on correspondingly high quantity it is also possible to order the LED-Light in white.

Based on the low power consumption of 50 W, the battery guarantees a runtime up to 15 hours, so you are never dependent on cables anymore.

Thanks to the choice of different PWM frequencies, the FX303 is even compatible with HD-Cameras.



Design

The battery operated IP65 led lamp is available in black and white. The compact and lightweight design allows multifunctional applications.



Electronics & Features

Channels	6 Channels: Zoom, Setting, RGBW 9 Channels: Strobe, Dimmer, Zoom, Setting, RGBW, CTO 12 Channels: Strobe, Dimmer, Zoom, Setting, Colourmacro, RGBW, CTO, Auto, AT-SP Fade
W-DMX	Built with Wireless Solution- or LumenRadio-Receiver
Display	4 colour LCD-Display for auto- and userdefined programms, Master-/Slavemode

Structure and Power supply

Battery autonomy	7 hours of Full White (RGBW) 15 hours constant colour change
Charging time	6 hours in flightcase



Contact

FEIMEX Ltd.

T +49(0)40 468 991 790
office@feimex.com
www.feimex.com

Dealer stamp



FX BatmooZ

Optical system

Beam angle 8° to 40°



LED-light sources

LEDs 4x red, 4x green, 4x blue, 4x white

Colours 16,7 million [R, G, B] 0 - 100 % saturation adjustable

Colour mixing RGBW

Temperature ranges

Operating temperature - 20° C ~ + 40° C

Cooling convection-cooled



Control & programming

Protocol DMX512 & W-DMX

Strobo 0 - 20 Hz

DMX-Channels 6, 9, 12 for advanced or basic controlling

Specifications

Mains voltage 100V ~ 240V

Power consumption 50W

DMX512-connection XLR 3-pol input/output

Housing

Material injection-moulded aluminum and plastic

Colour black or white (requires high quantity)

Protection class IP65

Dimensions / weight

Dimensions [L x W x H] 240 x 191 x 286 mm

Weight 6 kg (incl. battery)

